

Cam Spray Model 2000QE Q Series Oil Fired Hot Water Pressure Washer

- Triplex plunger pump with ceramic plungers and stainless steel valves.
- Adjustable pressure
- Adjustable Thermostat and pressure pop-off
- Chemical Injection
- Trigger Gun
- Dual wand with side handle and detergent tip
- Quick change tips in 0°,15°,25° and 40°
- Totally enclosed motor on electric models
- Powder coated frame with wand/hose rack
- 13" pneumatic tires with tube
- Schedule 80 coil with stainless cold wrap
- Rust free burner fuel tank
- Oil fired burner uses diesel fuel or kerosene to achieve a 140° fahrenheit rise in water temperature
- Look for optional accessories like the swivel hose reel that mounts to the frame
- All hot water machines must be properly vented if operated indoors.
- Gas and diesel powered models are fully portable, no electricity required, equipped with 12 volt oil fired burner
- Battery not included on electric start models
- CETL approved to UL standards



Products Features:

- Product Dimensions : 54" x 32" x 49"
- Voltage/Amperage/Phase : 230 Volt / 28 Amp/ 1
- Horsepower : 5
- Operating Pressure in psi/bar : 2000 / 138
- Flow Rate in gpm/lpm : 4 / 15.2
- Pump Thermal Protection : Mechanical
- Maximum Pump Inlet Water Temperature : 140° F
- Hose Dimension : 50' X 3/8"
- Burner Fuel Tank Capacity : 9 Gallon
- Burner Fuel Type : #1, #2 Diesel or Kerosene
- Power Cord : 35' with GFCI

Cam Spray • 520 Brooks Road • Iowa Falls, IA 50126
Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com